









## Yuasa NP4-12 Industrial VRLA Battery

Sp	ecifica	tions
		T.

12 Nominal voltage (V) 20-hr rate Capacity to 10.5V at 20°C (Ah) 4 10-hr rate Capacity to 10.8V at 20°C (Ah) 3.7

#### **Dimensions**

Length (mm) 90 (±1) Width (mm) 70 (±1) Height over terminals (mm) 106 (±2) Mass (kg) 1.75

# **Terminal Type**

FASTON - Quickfit / release (JST where stated) 4.75

## **Operating Temperature Range**

Storage (in fully charged condition) -20°C to +60°C -15°C to +50°C Charge Discharge -20°C to +60°C

## Storage

Capacity loss per month at 20°C (% approx.) 3

#### **Case Material**

Standard ABS (UL94:HB) FR version available UL94:V0

## **Charge Voltage**

Float charge voltage at 20°C (V)/Block 13.65 (±1%) 2.275 (±1%) Float charge voltage at 20°C (V)/Cell Float Chg voltage tmp correction factor from std

20°C (mV)

20°C (mV)

Cyclic (or Boost) charge Voltage at 20°C (V)/Block 14.5 (±3%) Cyclic (or Boost) charge Voltage at 20°C (V)/Cell 2.42 (±3%) Cyclic Chg voltage tmp correction factor from std -4

### **Charge Current**

Float charge current limit (A) No limit Cyclic (or Boost) charge current limit (A) 1

## **Maximum Discharge Current**

1 second (A) 120 1 minute (A) 40

# **Impedance**

Measured at 1 kHz (m $\Omega$ ) 40

#### **Design Life & Approvals**

**EUROBAT Classification: Standard Commercial** 3 to 5 Yuasa design life at 20°C (yrs) up to 5

## Art. no: SAANP4-12



#### Layout



## **3rd Party Certifications**

ISO9001 - Quality Management Systems UNDERWRITERS LABORATORIES Inc.





# Safety

#### Installation

Can be installed and operated in any orientation except permanently inverted.

#### **Handles**

Batteries must not be suspended by their handles (where fitted).

## Vent valves

Each cell is fitted with a low pressure release valve to allow gasses to escape and then reseal.

## Gas release

VRLA batteries release hydrogen gas which can form explosive mixtures in the air. Do not place inside a sealed container.

#### Recycling

YUASA's VRLA batteries must be recycled at the end of life in accordance with local and national laws and regulations.











